



FEEL THE FUTURE OF **CONNECTIVITY**





Designed to enable the **Smart Factory of Tomorrow**, Cleco introduces the **most advanced cordless nutrunner, CellTek**.[™]

Connectivity - The most reliable realtime synchronization with manufacturing and engineering systems

Ergonomic - Sleek and lightweight for the ultimate in comfort and balance

Speed - Improve your production time with the fastest cordless assembly tools in its class

Accurate - Ensures safety-critical assembly with best-in-class accuracy and repeatability

FEEL THE FUTURE OF CONNECTIVITY 🔊

Cleco's new **CellTek[™] Cordless Assembly Tools** bring superior connectivity, with the most reliable real-time syncronization with manufacturing and engineering systems. Designed to ensure safety-critical assembly with best-in-class accuracy, they are also the fastest cordless assembly tools in its class.



CellTek[™] | CORDLESS ASSEMBLY TOOLS

Safety/Accuracy

Repeatability of 2.0 cm/cmk @ +/-7% accuracy for safety critical joints





Flexible

Easily connects over Wifi (2.4 & 5.0 GHz) or Bluetooth 4.0

Decreased Takt Times Patented motor technology allows increased speeds over other battery platforms

Reduce Down-time

Exchange tools in seconds by swapping all wireless parameters and run down results on the line using the SmartSwap card

Multi-Color LED

Work light for secondary "ok/not ok" operator feedback while also illuminating your workpiece

Enhanced WiFi Range

Up to 300 feet for a broad connection within your production facility

minin

Stay Alive Function

0

Prevents reboot during battery change, gaining time and efficiency

mm

Cost Savings Connect up to 16 tools to

1 controller



Compatibility

Forward and backward compatibility with Cleco's entire Global cordless Controller platforms



FEEL THE FUTURE OF **CONNECTIVITY**

LITHIUM

ME

(111



RIGHT ANGLE

	SPEED r/min	Nm		Ft-lb		WEIGHT*	LENGTH	SIDE TO	HEIGHT		
MODEL NUMBER		Min Torque	Max Torque	Min Torque	Max Torque	kg (lb)	mm (in)	CENTER mm (in)	mm (in)	OUTPUT	
CTBAW153	1025	3.6	15	2.7	11.1	1.4 (3.1)	515 (20.28)	14.3 (0.56)	38.7 (1.52)	3/8" Square Drive	
CTBAW213	735	5.2	21	3.8	15.5	1.4 (3.1)	515 (20.28)	14.3 (0.56)	38.7 (1.52)	3/8" Square Drive	
CTBAW273	560	6.8	27	5.0	19.9	1.4 (3.1)	515 (20.28)	14.3 (0.56)	38.7 (1.52)	3/8" Square Drive	
CTBAW383	395	10	38	7.4	28.0	1.55 (3.4)	525 (20.60)	16.5 (0.65)	44.5 (1.75)	3/8" Square Drive	
CTBAW503	285	13	50	9.6	36.9	1.6 (3.5)	534 (21.02)	17 (0.67)	43.8 (1.72)	3/8" Square Drive	
CTBAW653	220	17	65	12.5	47.9	1.7 (3.7)	543 (21.38)	19 (0.75)	46.8 (1.84)	3/8" Square Drive	

*weight values do not include battery

PISTOL



	SPEED	Nm		Ft-lb		WEIGHT*	LENGTH	SIDE TO	HEIGHT		
MODEL NUMBER	r/min	Min Torque	Max Torque	Min Torque	Max Torque	kg (lb)	mm (in)	CENTER mm (in)	mm (in)	OUTPUT	
CTBPW05Q	3525	1.1	4.9	0.8	3.6	0.90 (2.0)	191 (7.52)	19.3 (0.76)	210 (8.27)	1/4" Quick Change	
CTBPW10Q	1600	2.4	10	1.8	7.4	0.95 (2.1)	207 (8.15)	19.3 (0.76)	210 (8.27)	1/4" Quick Change	
CTBPW15Q	1125	3.4	14.4	2.5	10.6	0.95 (2.1)	207 (8.15)	19.3 (0.76)	210 (8.27)	1/4" Quick Change	

*weight values do not include battery



CONTROLLERS[†]

MODEL NUMBER	DESCRIPTION	TOOL COMPATIBILITY	WEIGHT kg (lb)	WIDTH mm (in)	HEIGHT mm (in)	DEPTH mm (in)	
mPro200GC	Controller	CellTek, LiveWire, I-Wrench	3.23 (7.1)	113 (4.4)	340 (13.4)	320 (12.6)	
mPro200GC-AP	Controller with Access Point	CellTek, LiveWire, I-Wrench	3.43 (7.5)	113 (4.4)	340 (13.4)	320 (12.6)	
mPro200GC-G	Controller (Global)	CellTek, LiveWire, I-Wrench	3.23 (7.1)	113 (4.4)	340 (13.4)	320 (12.6)	
mPro200GC-AP- G	Controller with Access Point (Global)	CellTek, LiveWire, I-Wrench	3.43 (7.5)	113 (4.4)	340 (13.4)	320 (12.6)	
also compatible with the mPro400 Global Controller Platform							

BATTERIES AND CHARGERS

MODEL NUMBER	DESCRIPTION
T50-1000497	18V, 2.0Ah Battery (.43kg/.94lb)
T50-1000498	18V, 5.0Ah Battery (.72kg/1.60lb)
T50-1000499	18V Rapid Charger (NA)
T50-1000500	18V 6-Bay Sequential Charger (NA)
T50-1000506	18V Rapid Charger (Europe, Middle East, Africa)
T50-1000507	18V Charger (Brazil)
T50-1000508	18V 6-Bay Sequential Charger (Europe, Middle East, Africa)
T50-1000543	18V Charger (Argentina)
T50-1000544	18V Rapid Charger (United Kingdom)
T50-1000545	18V Rapid Charger (China)
T50-1000546	18V Rapid Charger (Japan)
T50-1000547	18V 6-Bay Sequential Charger (United Kingdom)

ACCESSORIES

MODEL NUMBER	DESCRIPTION
TBD	CellTek Barcode Scanner
TBD	CellTek Gyroscope
TBD	CellTek Ubisense Tracker Adapter
TBD	CellTek Barcode Scanner/Ubisense Combo









Apex Tool Group, LLC. www.ClecoTools.com / www.ClecoTools.de