

Product Specifications

CTBAW503

50 Nm RIGHT ANGLE

13 - 50 Nm (9.6 - 36.9 ft·lbs)

Designed to enable the Smart Factory of Tomorrow, Cleco introduces the most advanced cordless nutrunner - CellTek.™

FEATURES

- On-Tool Storage Back-up on-tool data collection in the event of disrupted connection
- Cost Savings Connect up to 16 tools to 1 controller
- Flexible Easily connects over Wifi (2.4 & 5.0 GHz) or Bluetooth 4.0
- Multi-Color LED Work light for secondary "ok/not ok" operator feedback while also illuminating your workpiece
- Compatibility Forward and backward compatibility with Cleco's entire Global cordless Controller platforms
- Stay Alive Function Prevents reboot during battery change, gaining time and efficiency
- Enhanced WiFi Range Up to 300 feet for a broad connection within your production facility
- Decreased Takt Times Patented motor technology allows increased speeds over other battery platforms

SPECIFICATIONS

TORQUE RANGE (Nm)

Min / Max: 13 - 50

TORQUE RANGE (ft-lb)

Min / Max: 9.6 - 36.9

SPEED

r/min: 285

WEIGHT & DIMENSIONS

Weight w/o Battery

Length

534 mm / 21.02 in

Height

43.8 mm / 1.72 in

Side to Center

17 mm / 0.67 in


Output

3/8" Square Drive

Country of Origin:

Assembled in USA







Phone: +1 (800) 845-5629 Phone: +1 (919) 387-0099 Phone: +49 (0)7363 81-0 www.ClecoTools.com / www.ClecoTools.de

